

DIP DYEING MACHINE





FEATURES

This equipment is designed to dye all kinds of knitwear, which is made of stainless steel. Knitwear can be moved into upper and lower direction for more protection.

OPTIONAL :

- PLC System
- Fully Automatic
- Color Dozing Tank
- Heat Exchanger
- Main Tub Portion

SPECIFICATION

- **Capacity (As Per Your Requirements)**
- **Size : As Per Your Capacity**
- Tub sheets 3mm SS 316
- Tub side sheet 3mm SS 316 .
- Pillar SS 304 with SS square pipe size 3"x3"x 3 mm thickness.
- SS pipe ¾ inch seamless for steam coil.
- SS Sheet 6mm with SS Pipe 3mm Thickness for steam coil header.
- Steam coil Cover Sheet SS 1.2mm .
- Drive with hydraulic jack system 2.2kw original recondition
- Circulation pump with 3HP 1400rpm original recondition motor

- Color Dozing Tank with 2mm sheets with agitator size Height 24" x 24" dia(Optional)
- Agitator Motor 1 HP 900 RPM
- steam in 1 inch & out 1 inch
- Water filling 3 inch & water drain 6 inch.
- Steam , filling & Drain with pneumatic system
- Temperature gauge Manual & Auto
- Panel with new accessories
- Up & Down & Dip Control with Timer.
- Hanger drive Structure with 1 ½" SS pipe
- Main Drive real With SS pipe 3 inch Dia& 4 mm Thickness
- All Bearing New